

(19) World Intellectual Property
Organization
International Bureau



(43) International Publication Date
9 September 2005 (09.09.2005)

PCT

(10) International Publication Number
WO 2005/082749 A1

(51) International Patent Classification⁷: **B65G 17/00**

(21) International Application Number:

PCT/IB2005/000443

(22) International Filing Date: 18 February 2005 (18.02.2005)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
BO2004A000085 19 February 2004 (19.02.2004) IT

(71) Applicant (for all designated States except US):
AZIONARIA COSTRUZIONI MACCHINE AUTOMATICHE A.C.M.A [IT/IT]; Via Cristoforo Colombo, 1, I-40131 Bologna (IT).

(72) Inventors; and

(75) Inventors/Applicants (for US only): **BOLDRINI, Fulvio** [IT/IT]; Via Zerbinati, 11, I-44100 Ferrara (IT). **COI, Daniele** [IT/IT]; Via Giulio Verne, 1, I-40128 Bologna (IT).

(74) Agents: **BIANCIARDI, Ezio** et al.; Bognion S.p.A., Via Goito, 18, I-40126 Bologna (IT).

(54) Title: PRODUCTS FEEDING UNIT


(81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SM, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.

(84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IS, IT, LT, LU, MC, NL, PL, PT, RO, SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Published:

— with international search report

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.



WO 2005/082749 A1

(57) Abstract: Products (6) are fed in an ordered succession by a unit (100) comprising a conveyor unit (1) equipped with pockets (43, 53), an outfeed conveyor (3) on which products (6) advance in succession at a given pitch (p2), also a transfer unit (2) operating between the conveyor unit (1) and the outfeed conveyor (3). The conveyor unit (1) presents a first belt (4) and a second belt (5) placed one beside the other and equipped with independent motors (M1, M2), whilst the pockets (43, 53) are arranged in first and second groups, each comprising a given number (n) of pockets ordered at constant pitch (p1) and associated respectively with the first belt (4) and the second belt (5), so that the groups are alternated one with another along a predetermined path (P). The transfer unit (2) includes an elevating platform (19) by which products (6) are ejected from the pockets (43, 53) and transferred at regular intervals to the outfeed conveyor (3), and the motors of the first and second belts (4, 5) are interlocked to a control unit (90) such as will ensure that the passage of each pocket is timed to coincide with an ejection stroke of the elevating platform (19).